

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Comprim Aplic. Largo, length (± 25mm)		Cód. Cor Conductor Color del Conductor Conductor Color Code
	min	max	min	max	(mm)	(inches)	
	SPT-8501-AL	6,50	7,50	0.256	0.295	400	16
SPT-8502-AL	7,50	7,90	0.295	0.311	450	18	azul, azul, blue
SPT-8504-AL	6,40	7,40	0.252	0.291	400	16	azul, azul, blue
SPT-8506-AL	8,80	9,80	0.346	0.386	450	18	amarelo, amarillo, yellow
SPT-9495-AL	9,60	10,60	0.378	0.417	450	18	vermelho, rojo, red
SPT-9496-AL	11,0	12,00	0.433	0.472	450	18	laranja, naranja, orange
SPT-9500-AL	10,6	10,80	0.417	0.425	450	18	vermelho, rojo, red
SPT-9501-AL	11,20	12,20	0.441	0.480	450	18	laranja, naranja, orange
SPT-9502-AL	12,40	13,40	0.488	0.528	450	18	verde, verde, green
SPT-9503-AL	8,00	8,60	0.315	0.339	450	18	azul, azul, blue
SPT-9504-AL	16,00	17,00	0.630	0.669	600	24	vermelho, rojo, red
SPT-9505-AL	17,00	18,00	0.669	0.709	600	24	púrpura, rosa, pink
SPT-9506-AL	9,00	9,80	0.354	0.386	450	18	marron, marron, brown
SPT-9507-AL	9,40	10,20	0.370	0.402	450	18	púrpura, rosa, pink
SPT-9508-AL	9,60	10,40	0.378	0.409	450	18	preto, negro, black
SPT-9509-AL	10,00	10,80	0.394	0.425	450	18	cinza, gris, gray
SPT-9510-AL	10,80	11,70	0.425	0.461	450	18	amarelo, amarillo, yellow
SPT-9511-AL	12,80	14,20	0.504	0.559	450	18	vermelho, rojo, red
SPT-9512-AL	16,20	17,20	0.638	0.677	600	24	branco, blanco, white
SPT-9513-AL	16,40	17,60	0.646	0.693	600	24	lilás, lila, lilac
SPT-9515-AL	14,30	16,00	0.563	0.630	600	24	laranja, naranja, orange
SPT-9525-AL	18,00	19,50	0.709	0.768	600	24	vermelho, rojo, red