

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size			Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Cod. Color del Conductor Conductor Color Code
	min	max	min	max	CA (AAC)	CAA (ACSR)	Cb. Multiplex Neutro Nú mm2	(mm)	(inches)	
	SDE-9900-M	3,90	4,30	0.154	0.169	-----	8 - 6/1	-----	295	14
SDE-9900	3,90	4,30	0.154	0.169	-----	-----	10 CA	345	14	preto, negro, black
SDE-9500	4,29	5,04	0.169	0.198	-----	6 - 6/1	-----	305	12	azul, azul, blue
SDE-9501	4,85	5,40	0.191	0.213	-----	-----	16 CA	305	12	branco, blanco, white
SDE-9502	6,00	6,70	0.236	0.264	4 - 7f/h/w	4 - 6/1, 7/1	25 CA	330	13	laranja, naranja, orange
SDE-9504	7,10	7,90	0.280	0.311	2 - 7f/h/w	2 - 6/1, 7/1	35 CAL	395	16	vermelho, rojo, red
SDE-9505	8,50	9,50	0.335	0.374	-----	-----	50 CAL	435	17	verde, verde, green
SDE-9506	9,16	10,17	0.361	0.400	1/0 - 7f/h/w	1/0 - 6/1	-----	435	19	amarelo, amarillo, yellow
SDE-9507-70	9,80	10,85	0.386	0.427	-----	-----	70 CAL	535	21	preto, negro, black
SDE-9507	10,18	11,44	0.401	0.450	2/0 - 7f/h/w	2/0 - 6/1	-----	535	21	azul, azul, blue
SDE-9508	11,90	13,20	0.469	0.520	3/0 - 7f/h/w	3/0 - 6/1	95 CAL	670	26	laranja, naranja, orange
SDE-9509	13,60	15,30	0.535	0.602	4/0 - 7f/h/w	4/0 - 6/1, 18/1	120 CAL	710	28	vermelho, rojo, red