

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size (awg/mcm)		Cb. Multiplex Seção do Neutro Nú	Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Cod. Color del Conductor Conductor Color Code
	min	max	min	max	CA (AAC)	CAA (ACSR)	mm2	(mm)	(inches)	
	DDE-9586	4,00	4,50	0.182	0.203	-----	8 - 6/1	-----	400	16
DDE-9554	4,60	5,30	0.182	0.203	6 - 7f/h/w	6 - 6/1	-----	400	16	azul, azul, blue
DDE-9541	5,70	6,45	0.229	0.257	4 - 7f/h/w	4 - 6/1, 7/1	25 CA	430	17	laranja, naranja, orange
DDE-9542	7,30	8,20	0.290	0.325	2 - 7f/h/w	2 - 6/1, 7/1	35 CAL	610	24	vermelho, rojo, red
DDE-9543	8,50	9,50	0.326	0.364	-----	-----	50 CAL	670	26	verde, verde, green
DDE-9544	9,15	10,25	0.365	0.409	1/0 - 7f/h/w	1/0 - 6/1	-----	670	26	amarelo, amarillo, yellow
DDE-9545-70	9,80	10,85	0.366	0.410	-----	-----	70 CAL	710	28	preto, negro, black
DDE-9545	10,30	11,55	0.410	0.460	2/0 - 7f/h/w	2/0 - 6/1	-----	710	28	azul, azul, blue
DDE-9546	11,60	13,00	0.461	0.516	3/0 - 7f/h/w	3/0 - 6/1	95 CAL	815	32	laranja, naranja, orange
DDE-9547	13,10	14,65	0.517	0.577	4/0 - 7f/h/w	4/0 - 6/1	120 CAL	865	38	vermelho, rojo, red
DDE-9548	14,10	15,60	0.578	0.615	266.8 - 7f/h/w	266.8 - 18/1	-----	890	35	preto, negro, black
DDE-9580	15,45	17,10	0.615	0.653	300 - 19f/h/w	266.8 - 26/7	-----	915	36	azul, azul, blue
DDE-9549	16,20	18,15	0.654	0.696	336.4 - 19f/h/w	300 - 26/7 336.4 - 18/1	-----	980	39	verde, verde, green
DDE-9581	17,40	19,30	0.697	0.739	397.5 - 19f/h/w	336.4 - 26/7	-----	1000	39	amarelo, amarillo, yellow
DDE-9550	18,90	21,00	0.740	0.837	397.5 - 19f/h/w 950 - 19f/h/w 477 - 19f/h/w 500 - 19, 37f/h/w	336.4 - 30/7 397.5 - 18/1, 30/7 397.5 - 26/7 477 - 18/1, 36/1	-----	1270	50	laranja, naranja, orange
DDE-9551	20,70	22,85	0.838	0.947	556.5 - 19f/h/w 636 - 37f/h/w 650 - 61f/h/w	477 - 24/7, 30/7 556.5 - 18/1, 26/7, 36/1 636 - 18/1	-----	1400	55	azul, azul, blue
DDE-9552	24,07	27,20	0.948	1.071	715.5 - 37f/h/w 750 - 61f/h/w 795 - 61f/h/w	666.6 - 36/1 715.5 - 36/1 795 - 36/1	-----	1475	62	marrom, marron, brown
DDE-9553	27,21	30,78	1.072	1.212	874.5 - 61f/h/w 954 - 61f/h/w 1033.5 - 61f/h/w	874.5 - 36/1 954 - 36/1 1033.5 - 36/1	-----	1680	70	laranja, naranja, orange