

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size (awg/ mcm)		Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Color del Conductor Conductor Color Code
	min	max	min	max	CA (AAC)	CAA (ACSR)	(mm)	(inches)	
	DDE/DF-7554	4,62	5,15	0.182	0.203	6 - 7f/h/w	6 - 6/1	1030	
DDE/DF-7541	5,81	6,53	0.229	0.257	4 - 7f/h/w	4 - 6/1,7/1	1030	41	laranja, naranja, orange
DDE/DF-7542	7,36	8,27	0.290	0.325	2 - 7f/h/w	2 - 6/1,7/1	1180	47	vermelho, rojo, red
DDE/DF-7544	9,27	10,40	0.365	0.409	1/0 - 7f/h/w	1/0 - 6/1	1180	47	amarelo, amarillo, yellow
DDE/DF-7545	10,41	11,69	0.410	0.460	2/0 - 7f/h/w	2/0 - 6/1	1230	48	azul, azul, blue
DDE/DF-7546	11,70	13,12	0.461	0.516	3/0 - 7f/h/w	3/0 - 6/1	1280	51	laranja, naranja, orange
DDE/DF-7547	13,13	14,67	0.517	0.577	4/0 - 7f/h/w	4/0 - 6/1	1310	52	vermelho, rojo, red