

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size (awg/ mcm)		Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Color del Conductor Conductor Color Code		
	min	max	min	max	CA (AAC)	CAA (ACSR)	(mm)	(inches)			
	DDE/DK-9554	4,62	5,15	0.182	0.203	6 - 7f/h/w	6 - 6/1	1070		43	azul, azul, blue
	DDE/DK-9541	5,81	6,53	0.229	0.257	4 - 7f/h/w	4 - 6/1,7/1	1070		42	laranja, naranja, orange
DDE/DK-9542	7,36	8,27	0.290	0.325	2 - 7f/h/w	2 - 6/1,7/1	1220	48	vermelho, rojo, red		
DDE/DK-9544	9,27	10,40	0.365	0.409	1/0 - 7f/h/w	1/0 - 6/1	1220	48	amarelo, amarillo, yellow		
DDE/DK-9545	10,41	11,69	0.410	0.460	2/0 - 7f/h/w	2/0 - 6/1	1240	49	azul, azul, blue		
DDE/DK-9546	11,70	13,12	0.461	0.516	3/0 - 7f/h/w	3/0 - 6/1	1320	52	laranja, naranja, orange		
DDE/DK-9547	13,13	14,67	0.517	0.577	4/0 - 7f/h/w	4/0 - 6/1	1340	53	vermelho, rojo, red		