

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size (awg/ mcm)		Marca Ident. Isol. Marca Ident. Aisl. Insul. Ident. Mark	Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Color del Conductor Conductor Color Code
	min	max	min	max	CA (AAC)	CAA (ASCR)	Ø75mm	(mm)	(inches)	
	DTF-0200	4,82	5,47	0.190	0.215	-----	6 - 6/1	amarelo, amarillo, yellow	635	25
DTF-0202	5,70	6,45	0.224	0.254	4 - 7f/h/w	4 - 6/1, 7/1	amarelo, amarillo, yellow	635	27	laranja, naranja, orange
DTF-0204	7,30	8,20	0.287	0.323	2 - 7f/h/w	2 - 6/1, 7/1	amarelo, amarillo, yellow	700	31	vermelho, rojo, red
DTF-0205	9,15	10,25	0.360	0.404	1/0 - 7f/h/w	1/0 - 6/1	amarelo, amarillo, yellow	750	32	amarelo, amarillo, yellow
DTF-0206	10,30	11,55	0.406	0.455	2/0 - 7f/h/w	2/0 - 6/1	amarelo, amarillo, yellow	720	26	azul, azul, blue
DTF-0207	11,60	13,00	0.457	0.512	3/0 - 7f/h/w	3/0 - 6/1	amarelo, amarillo, yellow	760	27	laranja, naranja, orange
DTF-0208	13,10	14,65	0.516	0.577	4/0 - 7f/h/w	4/0 - 6/1	amarelo, amarillo, yellow	800	29	vermelho, rojo, red
DTF-0208-M	14,80	16,30	0.575	0.634	266.8 - 19f/h/w 300 - 19f/h/w	266.8 - 18/1 266.8 - 26/7	amarelo, amarillo, yellow	840	34	azul, azul, blue
DTF-0209	16,20	18,15	0.638	0.715	336.4 - 19f/h/w 350 - 19f/h/w	300 - 26/7 336.4 - 18/1	amarelo, amarillo, yellow	840	34	verde, verde, green
DTF-0210	17,40	19,30	0.685	0.760	397.5 - 19f/h/w	336.4 - 26/7, 30/7 397.5 - 18/1	amarelo, amarillo, yellow	880	35	amarelo, amarillo, yellow
DTF-0211	18,90	21,00	0.744	0.827	477 - 19, 37f/h/w 500 - 19, 37f/h/w	397.5 - 26/7, 30/7 477 - 18/1	amarelo, amarillo, yellow	920	37	laranja, naranja, orange
DTF-0212	20,70	22,85	0.815	0.900	556.5 - 19f/h/w 556.5 - 37f/h/w	477 - 26/7, 30/7 556.5 - 18/1	amarelo, amarillo, yellow	950	38	azul, azul, blue