

CATAL. código código number	Intervalo de Aplic. Rango Aplicación (mm)		Diameter Range (inches)		Cabo / Cable / Conductor Size (awg/ mcm)		Marca Ident. Isol. Marca Ident. Aisl. Insul. Ident. Mark	Comprim. Aplic. Largo, Length (± 25mm)		Cód. Cor Conductor Color del Conductor Conductor Color Code
	min	max	min	max	CA (AAC)	CAA (ACSR)	Ø75mm	(mm)	(inches)	
	ISTF-0150	4,82	5,47	0.190	0.215	-----	6 - 6/1	amarelo, amarillo, yellow	450	18
ISTF-0152	5,70	6,45	0.224	0.254	4 - 7f/h/w	4 - 6/1, 7/1	amarelo, amarillo, yellow	500	21	laranja, naranja, orange
ISTF-0154	7,30	8,20	0.287	0.323	2 - 7f/h/w	2 - 6/1, 7/1	amarelo, amarillo, yellow	525	22	vermelho, rojo, red
ISTF-0155	9,15	10,25	0.360	0.404	1/0 - 7f/h/w	1/0 - 6/1	amarelo, amarillo, yellow	580	24	amarelo, amarillo, yellow
ISTF-0156	10,30	11,55	0.406	0.455	2/0 - 7f/h/w	2/0 - 6/1	amarelo, amarillo, yellow	630	26	azul, azul, blue
ISTF-0157	11,60	13,00	0.457	0.512	3/0 - 7f/h/w	3/0 - 6/1	amarelo, amarillo, yellow	720	29	laranja, naranja, orange
ISTF-0158	13,10	14,65	0.516	0.577	4/0 - 7f/h/w	4/0 - 6/1	amarelo, amarillo, yellow	730	30	vermelho, rojo, red
ISTF-0158-M	14,80	16,30	0.575	0.634	266.8 - 19f/h/w 300 - 19f/h/w	266.8 - 18/1 266.8 - 26/7	amarelo, amarillo, yellow	760	31	azul, azul, blue
ISTF-0159	16,20	18,15	0.638	0.715	336.4 - 19f/h/w 350 - 19f/h/w	300 - 26/7 336.4 - 18/1	amarelo, amarillo, yellow	780	31	verde, verde, green
ISTF-0160	17,40	19,30	0.685	0.760	397.5 - 19f/h/w	336.4 - 26/7, 30/7 397.5 - 18/1	amarelo, amarillo, yellow	820	33	amarelo, amarillo, yellow
ISTF-0161	18,90	21,00	0.744	0.827	477 - 19, 37f/h/w 500 - 19, 37f/h/w	397.5 - 26/7, 30/7 477 - 18/1	amarelo, amarillo, yellow	850	34	laranja, naranja, orange
ISTF-0162	20,70	22,85	0.815	0,000	556.5 - 19f/h/w 556.5 - 37f/h/w	477 - 26/7, 30/7 556.5 - 18/1	amarelo, amarillo, yellow	870	35	azul, azul, blue